

## Electric order picker

Brand		NEOlift
Model		NOPL
Power type		Battery
Operation type		Stand-on
Loading capacity	kg	2000
Loading center	mm	600
Tire type front/rear		PU/PU
Front wheel		Φ80×70
Driving wheel		Φ230×75
Balance wheel		Φ150×50
Wheel quantity Front/Rear(X=driving)		4/1X+2
Overall height	mm	1507
Max fork height	mm	110
Min. height	mm	85
Lift height	mm	195
Overall length	mm	2400
Overall width	mm	850
Fork size	l/e/s(mm)	1150/175/75
Overall width	mm	730
Stand height	mm	140
Fork outside width	mm	685
Body ground clearance	mm	55
Aisle(1000*1200mm pallet size)	Ast(mm)	3050
Turning radius	Wa(mm)	2250
Driving speed load/unload	km/h	6/6
Lifting speed load/unload	mm/s	29/33
Lowering speed load/unload	mm/s	23/18
Grade ability(S2 5)load/unload	%	5/5
Driving motor type		AC
Driving motor power(S2 60)	kw	1.5
Lifting motor type		DC
Lifting motor power(S3 15%)	kw	2.2
Battery V/AH	V/Ah	24/210
Battery weight	kg	200
Total weight(include battery)	kg	960
Steering type		Electric power steering
Parking brake type		Electromagnetism
Battery replacement method		Hoisting type